



Z-Select 2000D

Permanent Labels

Direct Thermal

Description:

A smooth, bright white, topcoated direct thermal label stock, which produces high contrast black images with Zebra thermal printers. The thermally sensitive top coating ensures maximum printhead life, gives superior smudge resistance and protects the label from environmental conditions. The adhesive gives good performance across a range of temperatures and on a wide variety of surfaces.

Note: Z-Select 2000D is not recommended for applications involving long term exposure to sunlight or extreme heat.

Suggested Applications

- Shelf edge labelling; product and price markdown labelling in Retail applications
- Sample labelling in Healthcare
- Picking and receiving labels in warehousing applications
- Box and pallet labelling
- Product identification
- Shipping labels
- Inspection labels for service engineers (mobile printing)

Technical Specifications

	Description	Caliper
Facestock	84gsm white topcoated thermal imaging paper	80 microns
Adhesive	Rubber based, permanent adhesive	15 microns
Liner	62gsm Glassine liner	56 microns
		Total 151 microns

Recommended Zebra Printers: Mobile, desktop, mid-range and high-performance thermal printers

Recommended Zebra ribbons: N/A

Minimum Application Temperature: -5°C

Service Temperature Range: -40°C to 50°C

Recommended Storage Conditions: Six months duration when stored at 0°C to 21°C at 35% to 50% RH

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, order from the Zipship price list or order sample roll SAM5311.

E

© 2007 ZIH Corp.